TMG POWER

DG 7500MSE





PORTABLE DIESEL GENSET

Continuous Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a constant electrical load.
Average load can be 100%. The generator must not be overloaded.

Standby Power

The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

Prime Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a variable electrical load.
Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Genset

Standby	**kVA**	7.5
Prime	**kVA**	6.8
Start System		Electric Start
Power Factor	**CosΦ**	1.0
Voltage		220 (50Hz)
Fuel Type		Diesel
Fuel Tank Capacity	**lt**	16

Engine

Model		186F
Kw (Standby/Prime)		5/4.6
Bore / Stroke	**mm**	86x72
Number of Cylinder		1
Oil Capacity	**lt**	1.6
Engine Type		4-Stroke, Air Cooled

Size

Weight	**kg**	155
L x W x H	**cm**	95 x 56 x 76

Mermerciler Sanayi Sitesi 3. Cadde No: 7 /B Beylikduzu / ISTANBUL / TURKEY
www.tmgpower.com.tr
+90 212 641 94 21 | info@tmgpower.com.tr

TMG POWER